



Modular Ice Machine up to 215 kg

Item #: Project: Quantity:



FEATURES

- Vertical Cube System.
- T304 Stainless Steel Panels.
- Auto-alert Indicator Lights.
- Global standard footprint: strictly follows international imperial standards commonly adopted in the industry of reference.
- One touch cleaning: reduces labor costs and saves time and simplifies cleaning process.
- Front evaporator access: immediate access to the evaporating plate for quick self-maintenance operations.
- Stackable: add flexibility!



NW 458 Full Cube 12 g W 26,5 x D 26,5 x H 26 mm



NW H 458 Half Cube 6 g W 13 x D 26,5 x H 26 mm

CONDENSING SYSTEM	RECOMMENDED BINS				
	Head	Bins		kg	
Air cooled	NW 458	✓	SB393	181	
		✓	SB530	243	
		CBT48EAMCD	SB948	406	

REFRIGERANT GAS

R404A

VOLTAGE V/Hz/ph

230/50/1

LEGENDA:

✓ : Perfect combination between ice maker and bin : Ice chute cut-out performed upon installation CBTxxxxxxxxxx : need additional bin top

Certifications:

OPERATING REQUIREMENTS



	Minimum	Maximum
Air temperature	10°C	43°C
Water temperature	5°C	38°C
Water pressure	1 bar (14 psi)	5 bar (70 psi)
Electrical voltage	-10%	+10%

IMPORTANT NOTICE:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals. Download our free App Scotsman Ice Apple store Google play Windows store

www.scotsman-ice.it www.scotsman-ice.com


NW 458








Modular Ice Machine up to 215 kg

Item #: Project: Quantity:









UNIT OF MEASUREMENT: \boldsymbol{mm}

- 1. Ø 20 mm WATER DRAIN
- 2. 3/4" GAS WATER INLET
- 3. CORD SET

UNIT DATA	
Size (W x D x H)	

760 x 620 x 575 mm

Net weight

73 kg

		Compressor		Circuit	Max. fuse size	
Version	Voltage	Btu/h	W	No.	Ømm²	Α
NW H 458 AS	230/50/1	8872	2600	3	1.5	16
NW L 458 AS	230/50/1	8872	2600	3	1.5	16

SHIPPING DATA

Carton (W x D x H)

830 x 690 x 770 mm

Weight

87 kg

			24 h ice production kg °C Amb. / °C Water		Energy consumption*		Water usage*	Instant power	
Version	Condensation	Voltage	10°C/10°C	21°C/10°C	32°C/21°C	kWh/100 kg	kWh/24h	l/h	W
NW H 458 AS	Air	230/50/1	215	200	146	14.2	23.3	10.8	1000
NW L 458 AS	Air	230/50/1	215	200	146	14.2	23.3	10.8	1000

^(*) Data refer to 32°C Amb. / 21°C Water temperature conditions